

ZETOR PROXIMA PLUS

MODEL	UNITS	90	100	110
ENGINE				
Model		Zetor 1205	Zetor 1005	Zetor 1305
Homologated power 2000/25	kW/HP	64,3/87	70,4/96	78,4/107
Rated speed	rpm		2200	
No. of cylinders			4	
Aspiration			turbocharged	
Bore/Stroke	mm		105/120	
Displacement	cc		4156	
Torque reserve	%		35	
Emissions			TIER III	
CLUTCH				
Type			dry, single plate, hydraulic control	
Diameter	mm		310	
Lining			cerametallic	
TRANSMISSION				
Type			two-stage power shift	
Shifting			fully synchronised	
Gears forward/reverse			16/16	
Speed	kmph	30 and 40	40	
PTO SHAFT				
Type			live/ground speed, wet multi-plate PTO clutch	
Speeds	rpm		540/1000 (540/540E)	
Front PTO - speed	rpm		+1000 (-1000), optional	
HYDRAULICS				
Type			mechanical, top link draft sensing	
Three point linkage			category II	
Control			position, draft, mixed	
Lift capacity	kN		42	
Operating pressure	MPa		19	
Pump capacity	(l/min)		50	
SCVs			three set of remotes standard	
OTHER				
Drive system			4WD	
Operator's station			cab version	
Steering			hydrostatic	
Service brake			wet disc brake, hydraulic control	
Parking brake			mechanical control	
Front axle 4WD			Carraro 20.16, wet brakes in wheels	
Rear axle			differential lock engaged electro-pneumatically	
DIMENSIONS				
Length	mm		3670	
Width	mm		1910	
Height	mm		2718	
Wheel base	mm		2328	
Ground clearance	mm		402	
Standard front tyres			380 / 70 R24	380 / 70 R24
Standard rear tyres			420 / 85 R34	480 / 70 R34
Weight	kg		3740	
OPTIONAL				

- adjustable steering wheel ■ A/C ■ adjustable trailer hitch ■ pick-up hitch ■ Grammer air suspended seats ■ passenger seat
- front and rear weights ■ hydraulic or air trailer brakes ■ choice of tyre combinations ■ carbon filters ■ hydraulic oil drain
- flashing beacon ■ block heater ■ heated rear window



Dealer: