

# ZETOR PROXIMA POWER

MODEL	UNITS	90	100	110	120
<b>ENGINE</b>					
Model		Zetor 1205	Zetor 1005	Zetor 1305	Zetor 1405
Homologated power 2000/25	kW/HP	64,3/87	70,4/96	78,4/107	86,2/117
Rated speed	rpm	2200			
No. of cylinders		4			
Aspiration		turbocharged			
Bore/Stroke	mm	105/120			
Displacement	cc	4156			
Torque reserve	%	35			37
Emissions		TIER III			
<b>POWER SHUTTLE</b>					
Type		multi disc wet clutch			
Control		electrohydraulically operated			
<b>TRANSMISSION</b>					
Type		three-stage power shift			
Shifting		fully synchronised			
Gears forward/reverse		24/24			
Speed	kmph	40			
<b>PTO SHAFT</b>					
Type		live/ground speed, wet multi-plate PTO clutch			
Speeds	rpm	540/1000 (540/540E)			
Front PTO - speed	rpm	+1000 (-1000), optional			
<b>HYDRAULICS</b>					
Type		mechanical, top link draft sensing			
Three point linkage		category II			
Control		position, draft, mixed			
Lift capacity	kN	42			
Operating pressure	MPa	19			
Pump capacity	(l/min)	50			
SCV's		three set of remotes standard			
<b>OTHER</b>					
Drive system		4WD			
Operator's station		cab version, noise 78 dB(A)			
Steering		hydrostatic			
Service brake		wet disc brake, hydraulic control			
Parking brake		mechanical control			
Front axle 4WD		Carraro 20.16, wet brakes in wheels			
Rear axle		differential lock engaged electro-pneumatically			
<b>DIMENSIONS</b>					
Length	mm	3905			
Width	mm	1910			
Height	mm	2718			
Wheel base	mm	2328			
Ground clearance	mm	402			
Standard front tyres		380 / 70 R24		380 / 70 R24	
Standard rear tyres		420 / 85 R34		480 / 70 R34	
Weight	kg	4000			
Fuel tank	l	175			
<b>OPTIONAL</b>					

- adjustable steering wheel   ■ A/C   ■ adjustable trailer hitch   ■ pick-up hitch   ■ front three point hitch   ■ front and rear ballast weights
- Grammer air suspended seats   ■ passenger seat   ■ hydraulic or air trailer brakes   ■ choice of tyre combinations   ■ carbon filters
- hydraulic oil drain   ■ block heater   ■ heated rear window



Dealer :