



NEW HOLLAND T3000

T3020 | T3030 | T3040



STYLISH VERSATILITY TO SUIT YOUR EVERY NEED.

New Holland T3000 Series tractors are built to meet the varied needs of agricultural, horticultural, ground care and municipal user. By combining powerful engines and hydraulics with a versatile mechanical 16x16 Synchro Shuttle™ transmission and 4WD front axle with 55 degree turn angle, these compact tractors define affordable versatility.



CLEAN, QUIET AND POWERFUL

With powers ranging from 43 to 54hp(CV), the Tier III powered T3000 Series match an excellent power to weight ratio with excellent fuel economy. With torque values as high as 191.5Nm, these tractors have the muscle for the most demanding of applications.



A COMPLETE TRACTOR PACKAGE

Look what T3000 can offer. A rear lift capacity of up to 1200kg. Up to three rear remote valves. A 540, 540E and ground speed PTO. Dedicated forward reverse shuttle lever. Then there are options to include a 400kg front linkage and PTO plus a wide choice of tyres.

T3000. Small in size. Big in value.

T3000. THE AFFORDABLE COMPACT ANSWER.



SETTING NEW STANDARDS FOR COMFORT AND ERGONOMICS.

Available in both cab and foldable ROPS versions, T3000 Series tractors offer high levels of operator comfort and safety. All controls are positioned so they are easy to reach. The high comfort seat adjusts to suit all sizes of operator. Access, from either side of the tractor, is clear and unrestricted. All the comfort you need from a compact tractor package.

SPECIFICATIONS

MODELS	T3O2O	T3O3O	T3O4O
Engine	Yanmar	Yanmar	Yanmar
No. of cylinders / capacity / valves / emissions level	4 / 1995 / 2 / Tier III	4 / 2189 / 2 / Tier III	4 / 1995 / 2 / Tier III
Aspiration	Natural	Natural	Turbocharged
Max. power ISO TR14396 - 2000/25/EC [kW/hp(CV)]	31.9/43.5	35/47.7	39.9/54.3
Rated engine speed (rpm)	2800	2800	2800
Maximum torque ECE R24 (Nm@rpm)	129@1400	141@120	195.5@2000
Cooling method	Liquid	Liquid	Liquid
Fuel tank capacity (L)	40	40	40
Transmission			
16x16 Synchro Shuttle™ transmission (with Creeper)	●	●	●
Minimum speed (m/h)	250	250	250
Maximum speed (km/h)	30	30	30
Front axle			
Four wheel drive (4WD)	●	●	●
Wheel turn angle (°)	55	55	55
Independent steering pump (18Lpm)	●	●	●
Turn radius 4WD (mm)	3500	3500	3500
Mechanical 4WD engagement	●	●	●
Electro-hydraulic differential lock (front / rear)	●	●	●
Rear hydraulic lift & PTO system			
Standard pump flow (Lpm)	28	28	28
Mechanical draft control	●	●	●
Rear lift capacity at ball ends (kg)	1200	1200	1200
Category 1 linkage	●	●	●
Max rear remotes	3	3	3
Rear PTO 540 / 540E	●	●	●
Front hydraulic lift & PTO system			
Front lift capacity at ball ends (kg)	400	400	400
Category 1 linkage	○	○	○
Fixed type link ends	○	○	○
Front PTO 1000rpm	○	○	○
Operator environment			
Rubber "silent blocks"	●	●	●
Deluxe seat	●	●	●
Suspended platform (with ROPS)	●	●	●
Cab	○	○	○
Heating and ventilation system	●	●	●
Air conditioning	○	○	○
Opening front and rear screens	●	●	●
Dimensions			
Wheelbase (mm)	1700	1700	1760
Front wheel track settings (mm)	1107 / 1357	1107 / 1357	1107 / 1357
Rear wheel track settings (mm)	1032 / 1262	1032 / 1262	1032 / 1262
Minimum overall width (mm)	1380	1380	1380
Minimum overall height - ROPS (mm)	1930	1930	1930
Minimum overall height - Cab (mm)	2140	2140	2140
Length with ballast (mm)	3300	3300	3360
Weight - ROPS (kg)	1460	1460	1480
Weight - Cab (kg)	1610	1610	1630

● Standard ○ Optional – Not available



YOUR SUCCESS - OUR SPECIALTY

AT YOUR OWN DEALER



NEW HOLLAND TOP SERVICE 00800 64 111 111

24/7 Support and Information

The call is free from a land line. Check in advance with your Mobile Operator if you will be charged. Alternatively call 01 2421881.

Visit our web site for UK: www.newholland.com/uk - for ROI: www.newholland.com/ie

The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by New Holland Brand Communications. Bts Adv. - Printed in Italy - 04/09 - TP01 - (Turin) - 80029/INB